Auto Iris Lens

02812DV

Focal Length		2.8 ~ 12mm	Mount/Flange Back	CS/M25.4X0.79
Max. Aperture Rate		1:1.4	Iris Control	Direct Drive
Image Format Cover		1/3"	Back Focal Length	-
Angle of View	D	93.95° ~ 28.07°	Temperature	-40°C ~ +50°C
	H	87.66° ~ 22.62°	Dimension(W	45.6×47×71.6mm
	V	65.47° ~ 17.06°	Weight	116g
Supply Voltage		DC6 ~ 12V		

0358DV

Focal Length		3.5 ~ 8mm	Mount/Flange Back	CS/M25.4X0.79
Max. Aperture Rate		1:1.4	Iris Control	Direct Drive
Image Format Cover		1/3"	Back Focal Length	8.2 ~ 12.9mm
Angle of View	D	81.20° ~ 41.10°	Temperature	-40°C ~ +50°C
	H	68.88° ~ 33.40°	Dimension(W	34.5×43×45.7mm
	V	54.43° ~ 25.36°	Weight	60g
Supply Voltage		DC6 ~ 12V		

0615DV

Focal Length		6 ~ 15mm	Mount/Flange Back	CS/M25.4X0.79
Max. Aperture Rate		1:1.4	Iris Control	Direct Drive
Image Format Cover		1/3"	Back Focal Length	12.2 ~ 19.5mm
Angle of View	D	53.13° ~ 22.62°	Temperature	-40°C ~ +50°C
	H	43.60° ~ 18.18°	Dimension(W	38×43.6×61mm
	V	33.40° ~ 13.69°	Weight	89g
Supply Voltage		DC6 ~ 12V		

0550DV

Focal Length		5 ~ 50mm	Mount/Flange Back	CS/M25.4X0.79
Max. Aperture Rate		1:1.4	Iris Control	Direct Drive
Image Format Cover		1/3"	Back Focal Length	10 ~ 12.5mm
Angle of View	D	61.93° ~ 6.87°	Temperature	-40°C ~ +50°C
	H	51.28° ~ 5.49°	Dimension(W	41×47×75.9mm
	V	39.6° ~ 4.12°	Weight	165g
Supply Voltage		DC6 ~ 12V		

05100DV

Focal Length		5 ~ 100mm	Mount/Flange Back	CS/M25.4X0.79
Max. Aperture Rate		1:1.8	Iris Control	Direct Drive
Image Format Cover		1/3"	Back Focal Length	6.6 ~ 8.3mm
Angle of View	D	61.93° ~ 3.44°	Temperature	-40°C ~ +50°C
	H	51.28° ~ 2.75°	Dimension(W	84.5×48×48.5mm
	V	39.6° ~ 2.06°	Weight	203.5g
Supply Voltage		DC6 ~ 12V		